



DACO SEMICONDUCTOR CO.,LTD.

**PFK3501(R)
THRU
PFK3505(R)**

INDUSTRIAL PRESS-FIT POWER RECTIFIERS TYPE 35A

Features

- High Surge Capability
- High Voltage Available
- Designed For A Wide Range of Application
- Leaded Version Available
- Types Up to 600V V_{RRM}
- Open junction


**35Amp Rectifier
50-600 Volts**

PRESS - FIT

Maximum Ratings

Operating Temperature: -65°C to $+190^{\circ}\text{C}$
Storage Temperature: -65°C to $+190^{\circ}\text{C}$

Part Number	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
PFK3501(R)	50V	35V	50V
PFK3502(R)	100V	70V	100V
PFK3503(R)	200V	140V	200V
PFK3504(R)	400V	280V	400V
PFK3505(R)	600V	420V	600V



Electrical Characteristics @ 25 °C Unless Otherwise Specified

Average Forward Current	$I_{F(AV)}$	35A	$T_C = 150^{\circ}\text{C}$
Peak Forward Surge Current	I_{FSM}	400A	8.3ms, half sine
Maximum Instantaneous Forward Voltage *	V_F	1.0V	$I_{FM} = 35A; T_A = 25^{\circ}\text{C}$
Maximum Instantaneous DC Reverse Current At Rated DC Blocking Voltage	I_R	5 uA 500uA	$T_A = 25^{\circ}\text{C}$ $T_A = 100^{\circ}\text{C}$
Maximum thermal resistance, junction to case	$R_{\theta jc}$	1.2 °C /w	

Notes:

- Standard Polarity: Lead is Cathode
- Reverse Polarity: Lead is Anode

DIM	DIMENSIONS				NOTE
	INCHES		MM		
	MIN	MAX	MIN	MAX	
A	0.501	0.505	12.73	12.82	
B	0.224	0.232	5.70	5.90	
C	0.433	0.512	11.00	13.00	
D	1.457	1.575	37.00	40.00	
E	0.050	0.051	1.27	1.29	

*Pulse Test: Pulse Width 300 usec, Duty Cycle 2%



FIG.1- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3- TYPICAL FORWARD CHARACTERISTICS




FIG.4- TYPICAL REVERSE CHARACTERISTICS

