



INDUSTRIAL PRESS-FIT POWER RECTIFIERS TYPE 25A

Features

- High Surge Capability
- High Voltage Available
- Designed For A Wide Range of Application
- Leaded Version Available
- Types Up to 1000V V_{RRM}
- Glass pasivated


25Amp Rectifier
50-1000 Volts

Maximum Ratings

Operating Temperature: -65°C to $+210^{\circ}\text{C}$
Storage Temperature: -65°C to $+210^{\circ}\text{C}$

Part Number	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
PFL2501G(R)	50V	35V	50V
PFL2502G(R)	100V	70V	100V
PFL2503G(R)	200V	140V	200V
PFL2504G(R)	400V	280V	400V
PFL2505G(R)	600V	420V	600V
PFL2506G(R)	800V	560V	800V
PFL2507G(R)	1000V	700V	1000V

PRESS - FIT LUCAS



Electrical Characteristics @ 25 °C Unless Otherwise Specified

Average Forward Current	$I_{F(AV)}$	25A	$T_C = 150^{\circ}\text{C}$
Peak Forward Surge Current	I_{FSM}	400A	8.3ms, half s
Maximum Instantaneous Forward Voltage *	V_F	1.10V	$I_{FM} = 25A;$ $T_J = 25^{\circ}\text{C}$
Maximum Instantaneous DC Reverse Current At Rated DC Blocking Voltage	I_R	10uA 200uA	$T_J = 25^{\circ}\text{C}$ $T_J = 150^{\circ}\text{C}$
Maximum thermal resistance, junction to case	$R_{\theta jc}$	1.2 °C /w	

Notes:

- Standard Polarity: Lead is Cathode
- Reverse Polarity: Lead is Anode

DIM	DIMENSIONS				NOTE
	INCHES		MM		
	MIN	MAX	MIN	MAX	
A	0.834	0.857	21.19	21.78	
B	0.336	0.343	8.53	8.70	
C	0.398	0.400	10.11	10.16	
D	0.050	0.051	1.29	1.30	

*Pulse Test: Pulse Width 300 usec, Duty Cycle 2%



FIG.1- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3- TYPICAL FORWARD CHARACTERISTICS




FIG.4- TYPICAL REVERSE CHARACTERISTICS

